
1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Identification of the preparation

Product Name: "JET-X 2% FOAM CONCENTRATE (High Expansion Foam Concentrate)"
Chemical Name: N/A – This is a mixture/preparation.
CAS No.: N/A – This is a mixture/preparation.
Chemical Formula: N/A – This is a mixture/preparation.
EINECS Number: N/A – This is a mixture/preparation.

1.2. Use of the preparation

The intended or recommended use of this preparation is as a FIRE EXTINGUISHING AGENT.

1.3. Company identification

Manufacturer/Supplier: ANSUL INCORPORATED
Address: One Stanton Street, Marinette, WI 54143-2542
Prepared by: Safety and Health Department
Phone: 715-735-7411
Internet/Home Page: <http://www.ansul.com>
Date of Issue: August, 2009

1.4. Emergency telephone

CHEMTREC 800-424-9300 or 703-527-3887

2. COMPOSITION/INFORMATION ON INGREDIENTS

- 2.1. Ingredient Name:** Proprietary mixture consisting of ammonium salts of fatty alcohol sulfates or ether sulfates (C8-C18), higher alcohols, and water.
Not otherwise specified.
- Chemical Formula:** N/A – This is a mixture/preparation.
CAS No.: N/A – This is a mixture/preparation.
EINECS Number: N/A – This is a mixture/preparation.
Concentration, Wt %: > 65 %.
Hazard Identification: See Heading 3.
- Ingredient Name:** Diethylene Glycol Monobutyl Ether (a).
Chemical Formula: C₄H₉O(CH₂CH₂O)₂H.
CAS No.: 112-34-5.
EINECS Number: 203-961-6.
Concentration, Wt %: 6 %.
Hazard Identification: See Heading 3.
- Ingredient Name:** Ethylene Glycol (a).
Chemical Formula: HOCH₂CH₂OH.
CAS No.: 107-21-1.
EINECS Number: 203-473-3.
Concentration, Wt %: 12 %.
Hazard Identification: See Heading 3.
- Ingredient Name:** Ammonium Lauryl Sulfate.
Chemical Formula: CH₃(CH₂)₁₀CH₂OSO₃NH₄.
CAS No.: 2235-54-3.
EINECS Number: 218-793-9.
Concentration, Wt %: 10-15 %.

(a) This chemical is subject to reporting requirements of SARA Title III Section 313 and 40 CFR Section 372.

NOTE: Unless a component presents a severe hazard, it does not need to be considered in the MSDS if the concentration is less than 1%. [According to Directive 1999/45/EC].

3. HAZARDS IDENTIFICATION

FOR HUMANS:

Product:

EU Classification:	Xi	Irritant.
R Phrases:	36/37/38	Irritating to eyes, respiratory, and skin.
S Phrases:	03	Keep in a cool place.
	15	Keep away from heat.
	21	When using, do not smoke.
	25	Avoid contact with eyes.
	26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	35	This material and its container must be disposed of in a safe way.
	45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Components:

Diethylene Glycol Monobutyl Ether:

EU Classification:	Xi	Irritant.
R Phrases:	36	Irritating to eyes.
S Phrases:	2	Keep out of the reach of children.
	24	Avoid contact with skin.
	26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Ethylene Glycol:

EU Classification:	Xn	Corrosive.
R Phrases:	22	Harmful if swallowed.
S Phrases:	2	Keep out of the reach of children.

Ammonium Lauryl Sulfate:

EU Classification:	Xi	Irritant.
R Phrases:	36/37/38	Irritating to eyes, respiratory, and skin.
S Phrases:	25	Avoid contact with eyes.
	26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Limit Values for Exposure:

Diethylene Glycol Monobutyl Ether:

OSHA PEL (General Industry) 8 hour TWA:	None established.
MAK (DE) Limit value:	100 mg/m ³ .
Short term exposure limit value (8 times, 5 minutes):	200 mg/m ³ .

Ethylene Glycol:

ACGIH TLV-CL:	100 mg/m ³ .
MAC (NL) Limit ceiling value:	125 mg/m ³ .
Limit value for EG particulates:	10 mg/m ³ .
Limit value for vapor:	26 mg/m ³ .
MAK (DE) Limit value:	26 mg/m ³ .
Short term exposure limit value (8 times, 5 minutes):	52 mg/m ³ .
OES (UK) Limit value:	60 mg/m ³ .
Limit value for EG particulates:	10 mg/m ³ .
Limit value for vapor:	125 mg/m ³ .

Neither this preparation nor the substances contained in it have been listed as carcinogenic by National Toxicology Program, I.A.R.C., or OSHA.

AS PART OF GOOD INDUSTRIAL AND PERSONAL HYGIENE AND SAFETY PROCEDURE, avoid all unnecessary exposure to the chemical substance and ensure prompt removal from skin, eyes, and clothing.

SIGNS AND SYMPTOMS:

Acute Exposure:

Eye Contact:	May cause mild transient irritation.
Skin Contact:	May cause mild transient irritation and/or dermatitis.
Inhalation:	Not a likely route of entry.
Ingestion:	Irritating to mucous membranes. Large oral doses may cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

Chronic Overexposure: Behavioral (sleep, motor, headache), lungs, gastrointestinal, liver, endocrine, blood, developmental.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Prior diseases of the liver.

FOR ENVIRONMENT:

NO harm to the environment is expected from an accidental release of this preparation. See Heading 12.

4. FIRST AID MEASURES

Eye Contact:	Wash with water for a minimum of 15 minutes. If irritation persists, seek medical attention.
Skin Contact:	Wash affected area with soap and water. If irritation persists, seek medical attention.
Inhalation:	Remove from exposure. If discomfort persists seek, medical attention.
Ingestion:	Do not induce vomiting. Risk of product entering the lungs on vomiting after ingestion. Seek medical attention.

5. FIRE-FIGHTING MEASURES

This preparation is an extinguishing media.
 There are NO extinguishing media which must not be used for safety reasons.
 NO special protective equipment is needed for fire-fighters.

6. ACCIDENTAL RELEASE MEASURES

For personal protection: Prevent skin and eye contact, see Heading 8.
 Clean up: Use an absorbent material such as diatomaceous earth, sawdust, etc., and sweep up, see Heading 13.
 NO harm to the environment is expected from an accidental release of this preparation. See Heading 12.

7. HANDLING AND STORAGE

7.1. Handling

Care should be taken in handling all chemical substances and preparations.
 See incompatibility information in Heading 10.

7.2. Storage

NO special conditions are needed for safe storage.
 See incompatibility information in Heading 10.
 Store in original container. Keep tightly closed until used.
 There is minimal danger to the environment from a storage release.

7.3. Specific use

The intended or recommended use of this preparation is as a FIRE EXTINGUISHING AGENT.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Exposure limit values

Diethylene Glycol Monobutyl Ether:	
OSHA PEL (General Industry) 8 hour TWA:	None established.
MAK (DE) Limit value:	100 mg/m ³ .
Short term exposure limit value (8 times, 5 minutes):	200 mg/m ³ .
Ethylene Glycol:	
ACGIH TLV-CL:	100 mg/m ³ .
MAC (NL) Limit ceiling value:	125 mg/m ³ .
Limit value for EG particulates:	10 mg/m ³ .
Limit value for vapor:	26 mg/m ³ .
MAK (DE) Limit value:	26 mg/m ³ .
Short term exposure limit value (8 times, 5 minutes):	52 mg/m ³ .
OES (UK) Limit value:	60 mg/m ³ .
Limit value for EG particulates:	10 mg/m ³ .
Limit value for vapor:	125 mg/m ³ .

8.2. Exposure controls

8.2.1. Occupational exposure controls

8.2.1.1. Respiratory protection

Mechanical ventilation is recommended.

Not normally necessary. Approved organic vapor respirator in absence of environmental controls.

8.2.1.2. Hand protection

Use chemical resistant gloves when handling the preparation.

8.2.1.3. Eye protection

Chemical goggles are recommended.

8.2.1.4. Skin protection

Standard fire fighting equipment should provide all protection which is necessary.

8.2.2. Environmental exposure controls

As much as possible, keep from being washed into surface water. See Heading 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. General information

Appearance: Clear blue colored liquid.
Odor: Mild sweet odor.

9.2. Important health, safety, and environmental information

pH: 6.0-7.0.
Boiling point/boiling range: 100 °C.
Flash point: None to boiling.
Flammability (solid/gas): Not flammable.
Explosive properties: Not explosive.
Oxidizing properties: Not an oxidizer.
Vapor Pressure: Not determined.
Relative Density (Water = 1): 1.02.
Solubility:
– Water solubility: Completely soluble.
– Fat solubility: Not soluble.
Partition coefficient, n-octanol/water: Not determined.
Viscosity: 190 cps.
Vapor density (Air = 1): Not determined.
Evaporation rate
(Butyl acetate = 1): Approximately 0.005.

9.3. Other information

Auto-ignition temperature: Does not ignite.

10. STABILITY AND REACTIVITY

10.1. Conditions to avoid

There are NO known conditions such as temperature, pressure, light, shock, etc., which may cause a dangerous reaction.

10.2. Materials to avoid

Reactive metals, electrically energized equipment, any material reactive with water, or strong oxidizers.

10.3. Hazardous decomposition products

Normally stable.

Hazardous polymerization will NOT occur.

Combustion or decomposition products include carbon monoxide and oxides of nitrogen and sulfur.

Hydrogen sulfide may be produced during bacterial decomposition under anaerobic conditions.

11. TOXICOLOGICAL INFORMATION

Product:	The toxicity of the product mixture has not been determined.		
Components:			
Diethylene glycol monobutyl ether:			
Toxicity Data:	Oral (rat) LD ₅₀	5,660 mg/kg.	[Dow Chemical Co.].
	Oral (rat) LD ₅₀	9,623 mg/kg.	[EINECS ESIS].
	Dermal (rabbit) LD ₅₀	4,000 mg/kg.	[Dow Chemical Co.].
	Dermal (rabbit) LD ₅₀	2,764 mg/kg.	[EINECS ESIS].
Irritation Data:	Eye (rabbit)	20 mg/day. Moderate.	[EINECS ESIS].
	Eye (rabbit) Draize test	Highly irritating.	[EINECS ESIS].
	Skin (rabbit)	1000 mg/kg/day. Moderate with edema, fissuring, and leathery appearance.	[EINECS ESIS].
Target organs:	Kidney, blood, liver, lungs, gastrointestinal, spleen.		
Diethylene Glycol Monobutyl Ether	did not interfere with reproduction. However, body weights of newborn animals were decreased.		
Ethylene glycol:			
Toxicity Data:	Oral (rat) LD ₅₀	4,700 mg/kg	
	Dermal (rabbit) LD ₅₀	9,530 ul/kg.	
Irritation Data:	Eye (rabbit)	555 mg Open	Mild.
	Skin (rabbit)	100 mg/1 hr	Mild.
Target organs:	Sense organs, kidney, liver, blood.		

12. ECOLOGICAL INFORMATION**12.1. Ecotoxicity**

Components:			
Diethylene glycol monobutyl ether:			
Fish,	Lepomis macrochirus:	LC ₅₀ (96 hrs)	1,300 mg/L.
	Carrassius auratus:	LC ₅₀ (24 hrs)	2,700 mg/L.
Daphnids,	Daphnia magna:	EC ₅₀ (24 hrs)	3,184 mg/L.
Algae,	Scenedesmus subspicatus:	EC ₅₀ (96 hrs)	>100 mg/L.
Ethylene Glycol:			
Fish,	Lepomis macrochirus:	LC ₅₀ (96 hrs)	27,540 mg/L.
	Poecilia reticulata:	LC ₅₀ (7 day)	49,300 mg/L.
Daphnids,	Daphnia magna:	EC ₅₀ (48 hrs)	57.6 g/L.
Algae,	Selenasstrum capricornutum:	EC ₅₀ (96 hrs)	6,500-13,000 mg/L.

12.2. Mobility

Diethylene glycol monobutyl ether:
Should not partition from a water column to organic matter contained in sediments and suspended solids.

Ethylene Glycol:
According to the calculations of a model, the estimated distribution of ethylene glycol is 97.9% in water, 2.1% in air, 0.0034% in soil, 0.0032% in sediment, and <5.2E-7% in suspended sediment or biota.

12.3. Persistence and degradability

Diethylene glycol monobutyl ether:
Indirect photodegradation is about 50 % in 3.5 hours.
Aerobic degradation with adapted activated sludge is 60 % after 28 days.
COD = 2080 mg/g substance.
BOD₅ = 250 mg O₂/g substance.
Theoretical oxygen demand = 2.17 mg/mg.

Ethylene Glycol:
Indirect photodegradation is about 50 % in 2.1 days.
Aerobic degradation with adapted activated sludge is 56 % after 28 hours.
COD = 1.19 mg/g substance.
BOD₅ = 0.78 mg O₂/L.
Theoretical oxygen demand = 2.17 mg/mg.

12.4. Bioaccumulative potential

Diethylene glycol monobutyl ether:
Should not bioaccumulate. Estimated bioaccumulation factor (log BCF) = 0.46.

12.5. Other adverse effects

Ozone depletion potential:	None.
Photochemical ozone creation potential:	None
Global warming potential:	None

13. DISPOSAL CONSIDERATIONS

NO harm to the environment is expected from an accidental release of this preparation. See Heading 12.
Dispose of in compliance with national, regional, and local provisions that may be in force.

14. TRANSPORT INFORMATION

Hazard Class or Division: Not hazardous.

For additional transport information, contact Ansul Incorporated.

NO harm to the environment is expected from an accidental release of this preparation. See Heading 12.

15. REGULATORY INFORMATION

EU Classification:	Xi	Irritant.
R Phrases:	36/37/38	Irritating to eyes, respiratory, and skin.
S Phrases:	03	Keep in a cool place.
	15	Keep away from heat.
	21	When using, do not smoke.
	25	Avoid contact with eyes.
	26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	35	This material and its container must be disposed of in a safe way.
	45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Limit Values for Exposure:

Diethylene Glycol Monobutyl Ether:

OSHA PEL (General Industry) 8 hour TWA: None established.

MAK (DE) Limit value: 100 mg/m³.

Short term exposure limit value
(8 times, 5 minutes): 200 mg/m³.

Ethylene Glycol:

ACGIH TLV-CL: 100 mg/m³.

MAC (NL) Limit ceiling value: 125 mg/m³.

Limit value for EG particulates: 10 mg/m³.

Limit value for vapor: 26 mg/m³.

MAK (DE) Limit value: 26 mg/m³.

Short term exposure limit value

(8 times, 5 minutes): 52 mg/m³.

OES (UK) Limit value: 60 mg/m³.

Limit value for EG particulates: 10 mg/m³.

Limit value for vapor: 125 mg/m³.

EINECS Status: All components are included in EINECS inventories or are exempt from listing.

EPA TSCA Status: All components are included in TSCA inventories or are exempt from listing.

Canadian DSL (Domestic Substances List): All components are included in the DSL or are exempt from listing.

Environmental restrictions: None are known.

Restrictions on Marketing and Use: None are known.

Refer to any other national measures that may be relevant.

16. OTHER INFORMATION

(HMIS) HAZARDOUS MATERIAL IDENTIFICATION SYSTEM RATINGS:

HEALTH:	<u>1</u>	4. Severe Hazard
FLAMMABILITY:	<u>0</u>	3. Serious Hazard
REACTIVITY:	<u>0</u>	2. Moderate Hazard
		1. Slight Hazard
		0. Minimal Hazard

(WHMIS) CANADIAN WORKPLACE HAZARDOUS MATERIAL IDENTIFICATION SYSTEM RATINGS:

This product is rated **D2A (Ethylene Glycol), D2B – Product may irritate eyes, skin or mucous membranes.**

Format is from directive 2001/58/EC.

EINECS data is from <http://exb.jrc.it/existing-chemicals/>

The EU Classification has been changed in accordance with Directive 1999/45/EC and information in the EINICS ESIS files (Existing Substances Information System).

Toxicological information added from the EINICS ESIS (Existing Substances Information System).

A rating under WHMIS has been added, following the Canadian guidelines.

17. DISCLAIMER

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT, BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. ANSUL SHALL NOT BE HELD LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT.

MSDS available at <http://www.ansul.com>

ANSUL is a trademark of Tyco International Ltd. or its affiliates.